

IN-LINE LUBRICATOR 3/4"



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 07:53 AM

SKU

: 17243

BRAND

: DIXON VALVE

MODEL

: PL400

Applications:

Designed to protect portable or stationary air tools by efficiently oiling the tool mechanisms.

Each time an air tool is operated, a fine mist of oil is injected into it along with the air from the compressor.

Use:

Type of oil to use: Use any petroleum-based, non-detergent light weight oil (SAE 10/150SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil.

Features:

Transparent sight disc allows visual inspection of oil level.

Oil flow regulated by screwdriver screw adjustment.

Minimum flow rate is 30 SCFM.

Construction:

Aluminum

Installation

Installation is recommended within 25 feet of the tool to be lubricated.

Refer to the arrow for proper air flow direction.

Safety notes:

Not recommended for constant flow applications. For reciprocating tools only.

Do not use any synthetic oil or oils containing additives or solvents.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|---------------------------|
| Capacity | 3.7 fluid oz. oil (105ml) |
| Factory Part Number | PL400 |
| Female Thread | NPT |
| Female Thread Size | 3/4" (20mm) |
| Flow | 70 SCFM |
| Material | Aluminum |
| Maximum Operating Pressure | 200 PSI at 70°F (21°C) |
| Weight Lb | 1.5800 |