

IN-LINE LUBRICATOR 3/4" LARGE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 04/21/2026 04:41 PM

SKU
: 17244

BRAND
: DIXON VALVE

MODEL
: PL400L

Applications:

Designed to protect portable or stationary air tools by efficiently oiling the tool mechanisms.

Each time an air tool is operated, a fine mist of oil is injected into it along with the air from the compressor.

Use:

Type of oil to use: Use any petroleum-based, non-detergent light weight oil (SAE 10/150SSU) which will readily break up into a mist, i.e., Mobil DTE light or comparable oil.

Features:

Transparent sight disc allows visual inspection of oil level.

Oil flow regulated by screwdriver screw adjustment.

Minimum flow rate is 30 SCFM.

Construction:

Aluminum

Installation

Installation is recommended within 25 feet of the tool to be lubricated.

Refer to the arrow for proper air flow direction.

Safety notes:

Not recommended for constant flow applications. For reciprocating tools only.

Do not use any synthetic oil or oils containing additives or solvents.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Capacity	11.0 fluid oz. oil (312.5ml)
Factory Part Number	PL400L
Female Thread	NPT
Female Thread Size	3/4" (20mm)
Flow	70 SCFM
Material	Aluminum
Maximum Operating Pressure	300 PSI at 70°F (21°C)
Weight Lb	2.5700