

TRUESEAL? BALL VALVE FEMALE CONNECTOR



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/27/2026 09:09 PM

SKU

: 17331

BRAND

: DIXON VALVE

MODEL

: PP6VFC2-MG

Applications:

These corrosion resistant, all-plastic designed ball valves are ideal for water filtration units, coffee and beverage machines and a wide variety of other fluid applications.

Specifications:

FDA compliant

NSF-51 listed for contact with food

Certified to NSF-61

Features:

EPDM seal secures connection with larger surface area than standard O-rings

Full flow self-cleaning ball

High-temperature, scale resistant Polysulfone ball

Construction:

Glass-reinforced Polypropylene body

O-ring seal material: EPDM

Safety notes:

Actual working pressures will be lower at elevated temperatures.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Burst Pressure	600 PSI
Factory Part Number	PP6VFC2-MG
Female Thread	NPTF
Female Thread Size	1/8"
Material	Polypropylene
Maximum Operating Pressure	150 PSI
Seal	EPDM
Temperature Range	0°F to 225°F (-18°C to 107°C)
Tube OD	3/8"
Weight Lb	0.0530