

**POLYPROPYLENE CAM & GROOVE TYPE C COUPLER X HOSE SHANK**



\* Referential image  
\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 06/16/2026 05:26 AM

SKU  
: 17369

BRAND  
: DIXON VALVE

MODEL  
: PPC300

Construction:  
304 stainless steel handles  
EPDM gaskets  
304 stainless steel pins

How it works:  
To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.  
Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Safety notes:  
Pressure rating recommendations are based on the use of mating Dixon® fittings at ambient temperature 70°F (21°C) with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon®.  
Polypropylene cam and groove should not be mixed with metal fittings.  
NOT recommended for use with PTFE gaskets  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Material</b>	Polypropylene
<b>Maximum Operating Pressure</b>	60 PSI
<b>Factory Part Number</b>	PPC300
<b>Seal</b>	EPDM
<b>Size</b>	3"
<b>Weight Lb</b>	1.2650

**TECHNICAL SPECIFICATIONS**