

POLYPROPYLENE CAM & GROOVE TYPE C COUPLER X HOSE SHANK



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 06/16/2026 05:24 AM

SKU
: 17372

BRAND
: DIXON VALVE

MODEL
: PPC75

Construction:
304 stainless steel handles
EPDM gaskets
304 stainless steel pins

How it works:
To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Safety notes:
Pressure rating recommendations are based on the use of mating Dixon® fittings at ambient temperature 70°F (21°C) with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon®.
Polypropylene cam and groove should not be mixed with metal fittings.
NOT recommended for use with PTFE gaskets
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Material	Polypropylene
Maximum Operating Pressure	125 PSI
Factory Part Number	PPC75
Seal	EPDM
Size	3/4"
Weight Lb	0.2350

TECHNICAL SPECIFICATIONS