

**POLYPROPYLENE CAM & GROOVE TYPE D COUPLER X FEMALE NPT**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 06/16/2026 05:25 AM

SKU

: 17385

BRAND

: DIXON VALVE

MODEL

: PPD200

Construction:

Manufactured from glass-filled polypropylene

EPDM Gaskets

304 stainless steel handles and pins

How it works:

To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.

Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Safety notes:

Pressure rating recommendations are based on the use of mating Dixon® fittings at ambient temperature 70°F (21°C) with a standard seal installed.

For use at elevated temperature or other unusual operating conditions, consult Dixon®.

NOT recommended for use with PTFE gaskets

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Material</b>	Polypropylene
<b>Maximum Operating Pressure</b>	100 PSI
<b>Factory Part Number</b>	PPD200
<b>Seal</b>	EPDM
<b>Size</b>	2"
<b>Weight Lb</b>	0.6000