

POLYPROPYLENE CAM & GROOVE TYPE D COUPLER X FEMALE NPT

DATE
: 06/16/2026 05:25 AM

SKU
: 17389

BRAND
: DIXON VALVE

MODEL
: PPD75

Construction:
Manufactured from glass-filled polypropylene
EPDM Gaskets
304 stainless steel handles and pins

How it works:
To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.
Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Safety notes:
Pressure rating recommendations are based on the use of mating Dixon® fittings at ambient temperature 70°F (21°C) with a standard seal installed.
For use at elevated temperature or other unusual operating conditions, consult Dixon®.
NOT recommended for use with PTFE gaskets
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|---------------|
| Material | Polypropylene |
| Maximum Operating Pressure | 125 PSI |
| Factory Part Number | PPD75 |
| Seal | EPDM |
| Size | 3/4" |
| Weight Lb | 0.1700 |



* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability