

## POLYPROPYLENE CAM & GROOVE TYPE F ADAPTER X MALE NPT



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 06/16/2026 06:01 AM

SKU

: 17404

BRAND

: DIXON VALVE

MODEL

: PPF400

Construction:

Manufactured from glass-filled polypropylene

How it works:

To make a connection, simply slide the adapter into the coupler and with normal hand pressure, press the cam levers down.

Uncoupling is as quick and simple as coupling. Just lift the cam arms and remove the adapter.

Safety notes:

Under no circumstances should cam and groove couplings be used for compressed air or steam service!

Pressure rating is based on the seal of the mating part

Pressure rating recommendations are based on the use of mating Dixon® fittings at ambient temperature 70°F (21°C) with a standard seal installed. For use at elevated temperature or other unusual operating conditions, consult Dixon®.

Polypropylene cam and groove should not be mixed with metal fittings.

NOT recommended for use with PTFE gaskets

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Material</b>	Polypropylene
<b>Maximum Operating Pressure</b>	50 PSI
<b>Factory Part Number</b>	PPF400
<b>Size</b>	4"
<b>Weight Lb</b>	1.0000