


## DQC HS-SERIES ISO-B STEAM INTERCHANGE FEMALE PLUG



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 08/28/2026 08:19 AM

SKU

: 25152

BRAND

: DIXON VALVE

MODEL

: PS-H12F12-B

Applications:

Designed exclusively for steam applications

Construction:

Machined components are manufactured using solid bar stock

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Special high-temp EPDM O-rings designed for steam service

Compatibility & Interchange Data:

Interchangeable to ISO7241 Series 'B'

Parker 60-Series Steam Couplings

Safety notes:

Maximum working pressure has been calculated using standard saturated steam at 194°C (382°F) for general purpose continuous service. For advanced operating pressure or super-heated steam applications, contact Dixon for further information.

Warning: Do not disconnect under pressure!

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

|                     |                                                      |
|---------------------|------------------------------------------------------|
| Body Size           | 1-1/2"                                               |
| Material            | Brass                                                |
| Factory Part Number | PS-H12F12-B                                          |
| Pressure Rating     | Rated to 200 PSI gauge saturated steam 382°F (194°C) |
| Temperature Range   | -70°F to +400°F (-57°C to +204°C)                    |
| Thread              | Female NPTF                                          |
| Thread Size         | 1-1/2" - 1 1/2"                                      |
| Weight Lb           | 3.1000                                               |