

**DQC E-SERIES STRAIGHT THROUGH INTERCHANGE MALE PLUG- RETAIL PACKAGE**



DATE  
: 04/29/2026 04:43 PM

SKU  
: 17700

BRAND  
: DIXON VALVE

MODEL  
: PW-E3M3

Features:

Straight-Through Pressure-Wash Interchange

Interchanges with Parker ST-Series, Foster FST-Series, Tomco Series-ST, Hansen ST-Series

These plugs have no internal valves, providing maximum flow with minimum pressure drop.

Construction:

Steel componentry is plated using ROHS Compliant Trivalent Chrome

Steel nipples are hardened to provide heavy duty performance.

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

Dixon cannot assume liability for misapplication of products resulting in equipment down-time, lost production, property damage and/or personal injury including death.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Body Size</b>	3/8"
<b>Burst Pressure</b>	14,000 PSI (966 Bar)
<b>Description</b>	3/8" straight thru nipples (Case Qty 20 Required)
<b>Hex</b>	3/4"
<b>Length</b>	1.69 (42.9mm)
<b>Male Thread</b>	NPTF
<b>Male Thread Size</b>	3/8"-18



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

## TECHNICAL SPECIFICATIONS

<b>Mandatory Pkg/Box Qty</b>	20
<b>Material</b>	Steel
<b>Maximum OD</b>	0.79 (20.1mm)
<b>Maximum Operating Pressure</b>	3,500 PSI (241 Bar)
<b>Factory Part Number</b>	PW-E3M3
<b>Weight Lb</b>	0.1000