

## WILKERSON FRL'S R18 COMPACT REGULATOR



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/09/2026 11:50 AM

SKU

: 26548

BRAND

: DIXON VALVE

MODEL

: R18-03R

Use:

To increase regulated pressure, pull adjusting knob up and turn clockwise.

To reduce pressure, turn knob counter clockwise.

Features:

0-125 PSI adjusting range

Self-relieving standard

Two 1/4" NPT gauge ports located on the front and rear faces of the body.

These ports may be used as additional regulated ports or for pressure gauges.

Available Options:

Available with 0-60 PSI adjusting range, contact Dixon for pricing and availability.

Installation

Can be installed with the adjusting knob in any position

Note:

Use a GC230 gauge (not supplied)

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 100 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	R18-03R
<b>Flow</b>	165 SCFM
<b>Includes</b>	Without Gauge
<b>Maximum Operating Pressure</b>	300 PSIG (20.7 Bar)
<b>Port</b>	3/8"
<b>Temperature Range</b>	32°F to 150°F (0°C to 65.5°C)
<b>Weight Lb</b>	1.5300