

WILKERSON FRL'S R18 COMPACT REGULATOR



DATE
: 04/24/2026 03:23 AM

SKU
: 26548

BRAND
: DIXON VALVE

MODEL
: R18-03R

Use:

To increase regulated pressure, pull adjusting knob up and turn clockwise.
To reduce pressure, turn knob counter clockwise.

Features:

0-125 PSI adjusting range
Self-relieving standard
Two 1/4" NPT gauge ports located on the front and rear faces of the body.
These ports may be used as additional regulated ports or for pressure gauges.

Available Options:

Available with 0-60 PSI adjusting range, contact Dixon for pricing and availability.

Installation

Can be installed with the adjusting knob in any position

Note:

Use a GC230 gauge (not supplied)

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 100 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Factory Part Number	R18-03R
Flow	165 SCFM
Includes	Without Gauge
Maximum Operating Pressure	300 PSIG (20.7 Bar)
Port	3/8"
Temperature Range	32°F to 150°F (0°C to 65.5°C)
Weight Lb	1.5300