

WILKERSON FRL'S R21 DIAL AIR REGULATOR



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability



DATE
: 07/09/2026 11:55 AM

SKU
: 26555

BRAND
: DIXON VALVE

MODEL
: R21-02RG

Use:

Dial regulators feature a transparent, pressure-calibrated, non-rising adjustment dial for quick adjustment of secondary pressure.

The full reduced pressure range can be dialed in less than 270° of dial rotation. This feature is particularly advantageous if secondary pressure must be changed frequently.

All dial-air units have a slight constant air bleed.

Features:

0-160 PSI adjusting range

Balanced valve design

Relieving type

Non-rising pressure adjusting dial

Piston operated

One 1/4" NPT gauge port standard, can be used for additional outlet ports

Includes a GC235 gauge

Installation

Dial air regulators can be mounted in any position so dial face is always visible.

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 100 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|-------------------------------|
| Factory Part Number | R21-02RG |
| Flow | 117 SCFM |
| Includes | With Gauge |
| Mandatory Pkg/Box Qty | 1 |
| Maximum Operating Pressure | 300 PSIG (20.7 Bar) |
| Port | 1/4" |
| Temperature Range | 32°F to 150°F (0°C to 65.5°C) |
| Weight Lb | 2.6200 |