

## WILKERSON FRL'S R21 DIAL AIR REGULATOR



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 04/24/2026 03:26 AM

SKU  
: 26556

BRAND  
: DIXON VALVE

MODEL  
: R21-03R

### Use:

Dial regulators feature a transparent, pressure-calibrated, non-rising adjustment dial for quick adjustment of secondary pressure.

The full reduced pressure range can be dialed in less than 270° of dial rotation. This feature is particularly advantageous if secondary pressure must be changed frequently.

All dial-air units have a slight constant air bleed.

### Features:

0-160 PSI adjusting range

Balanced valve design

Relieving type

Non-rising pressure adjusting dial

Piston operated

Two 1/4" NPT gauge ports standard, can be used for additional outlet ports

### Installation

Dial air regulators can be mounted in any position so dial face is always visible.

### Note:

Use a GC230 gauge (not supplied)

### Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 100 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	R21-03R
<b>Flow</b>	180 SCFM
<b>Includes</b>	Without Gauge
<b>Maximum Operating Pressure</b>	300 PSIG (20.7 Bar)
<b>Port</b>	3/8"
<b>Temperature Range</b>	32°F to 150°F (0°C to 65.5°C)
<b>Weight Lb</b>	2.3800