

WILKERSON FRL'S R21 DIAL AIR REGULATOR



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 04/24/2026 03:24 AM

SKU
: 26558

BRAND
: DIXON VALVE

MODEL
: R21-04R

Use:

Dial regulators feature a transparent, pressure-calibrated, non-rising adjustment dial for quick adjustment of secondary pressure.

The full reduced pressure range can be dialed in less than 270° of dial rotation. This feature is particularly advantageous if secondary pressure must be changed frequently.

All dial-air units have a slight constant air bleed.

Features:

0-160 PSI adjusting range

Balanced valve design

Relieving type

Non-rising pressure adjusting dial

Piston operated

Two 1/4" NPT gauge ports standard, can be used for additional outlet ports

Installation

Dial air regulators can be mounted in any position so dial face is always visible.

Note:

Use a GC230 gauge (not supplied)

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 100 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	R21-04R
Flow	195 SCFM
Includes	Without Gauge
Maximum Operating Pressure	300 PSIG (20.7 Bar)
Port	1/2"
Temperature Range	32°F to 150°F (0°C to 65.5°C)
Weight Lb	2.3000