

**WILKERSON FRL'S R26  
STANDARD REGULATOR**



DATE  
: 04/24/2026 05:04 AM

SKU  
: 26564

BRAND  
: DIXON VALVE

MODEL  
: R26-03RG

Use:

To increase regulated pressure, pull adjusting knob up and turn clockwise.  
To reduce pressure, turn knob counter clockwise.

Features:

- 0-125 PSI adjusting range
- Non-rising push/pull locking adjustment knob
- Panel mount nut standard
- Excellent flow characteristics
- One 1/4" NPT gauge port standard, can be used for additional outlet ports
- Supplied with a gauge

Installation

Can be installed with the adjusting knob in any position

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	R26-03RG
<b>Flow</b>	148 SCFM
<b>Includes</b>	With Gauge
<b>Mandatory Pkg/Box Qty</b>	1
<b>Maximum Operating Pressure</b>	300 PSIG (20.7 Bar)
<b>Port</b>	3/8"
<b>Temperature Range</b>	32°F to 150°F (0°C to 65.5°C)

\* Referential image  
\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

**Weight Lb**

2.7600