

## WILKERSON FRL'S R28 STANDARD REGULATOR



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 04/24/2026 05:07 AM

SKU  
: 26571

BRAND  
: DIXON VALVE

MODEL  
: R28-03R

Use:  
To increase regulated pressure, pull adjusting knob up and turn clockwise.  
To reduce pressure, turn knob counter clockwise.

Features:  
0-125 PSI adjusting range  
Self-relieving standard  
Four adjusting pressure ranges available  
Two 1/4" NPT gauge ports located on the front and rear faces of the body.  
These ports may be used as additional regulated ports or for pressure gauges.

Note:  
Use a GC230 gauge (not supplied)

Safety notes:  
FRL's are designed for air service only, unless otherwise indicated.  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	R28-03R
<b>Flow</b>	228 SCFM
<b>Includes</b>	Without Gauge
<b>Maximum Operating Pressure</b>	300 PSIG (20.7 Bar)
<b>Port</b>	3/8"
<b>Temperature Range</b>	32°F to 150°F (0°C to 65.5°C)
<b>Weight Lb</b>	1.6000

**TECHNICAL SPECIFICATIONS**