

WILKERSON FRL'S R30 HIGH PRESSURE HIGH FLOW REGULATOR



DATE
: 04/24/2026 06:57 AM

SKU
: 26580

BRAND
: DIXON VALVE

MODEL
: R30-06RHG

Use:
To increase regulated pressure, pull adjusting knob up and turn clockwise.
To reduce pressure, turn knob counter clockwise.

Features:
0-180 PSI adjusting range
Self-relieving standard
Piston operated
One 1/4" NPT gauge port standard, can be used for additional outlet ports
Includes a GC240 gauge

Installation
Can be installed with the adjusting knob in any position

Safety notes:
FRL's are designed for air service only, unless otherwise indicated.
SCFM ratings at 100 PSIG inlet pressure
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	R30-06RHG
Flow	480 SCFM
Includes	With Gauge
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	300 PSIG (20.7 Bar)
Size	3/4"
Temperature Range	32°F to 150°F (0°C to 65.5°C)

* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Weight Lb

6.1900