

WILKERSON FRL'S R30 HIGH PRESSURE HIGH FLOW REGULATOR



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/24/2026 07:00 AM

SKU

: 26584

BRAND

: DIXON VALVE

MODEL

: R30-08RHG

Use:

To increase regulated pressure, pull adjusting knob up and turn clockwise.

To reduce pressure, turn knob counter clockwise.

Features:

0-180 PSI adjusting range

Self-relieving standard

Piston operated

One 1/4" NPT gauge port standard, can be used for additional outlet ports

Includes a GC240 gauge

Installation

Can be installed with the adjusting knob in any position

Safety notes:

FRL's are designed for air service only, unless otherwise indicated.

SCFM ratings at 100 PSIG inlet pressure

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	R30-08RHG
Flow	500 SCFM
Includes	With Gauge
Mandatory Pkg/Box Qty	1
Maximum Operating Pressure	300 PSIG (20.7 Bar)
Size	1"
Temperature Range	32°F to 150°F (0°C to 65.5°C)

- Page 1/2 -

TECHNICAL SPECIFICATIONS

Weight Lb

5.9300