

## GROOVED RIGID COUPLING- SERIES R, STYLE 5



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/22/2026 03:00 PM

SKU

: 17813

BRAND

: DIXON VALVE

MODEL

: R725BU

Applications:

Ideal for fire protection, plumbing, low pressure air and drainage.

Specifications:

Underwriters Listed

Factory Mutual approved

Bolts: 2

Bolt Size: 3/8"

Bolt Length: 2"

Features:

Lightweight and low pressure

Small gripping teeth hold the housing into the groove allowing a straight run of pipe and preventing any flex at the joint.

Construction:

Galvanized ductile iron body

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	R725BU
<b>Material</b>	Ductile Iron
<b>Max. End Load Lbs.</b>	6490
<b>Maximum Operating Pressure</b>	175 PSI at 70°F (21°C)
<b>Nominal Size</b>	2-1/2"
<b>Pipe OD</b>	2.875"
<b>Seal</b>	Buna-N
<b>Weight Lb</b>	1.7500