

AG-SERIES BALL PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 02:45 AM

SKU

: 27615

BRAND

: DIXON VALVE

MODEL

: RD-AG4F4

Construction:

Machined components are manufactured using solid bar stock

Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:

Pioneer Agricultural Interchange

Parker/Pioneer 4000 Series, Faster NS/NV Series

Safeway Series-S20, Stucchi IR-Series

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Burst Pressure	16500 PSI (1100 Bar)
Hex	1-1/16"
Length	1.95" (49.5mm)
Mandatory Pkg/Box Qty	4
Material	Steel
Maximum OD	1.21" (30.7mm)
Maximum Operating Pressure	4000 PSI (275 Bar)
Factory Part Number	RD-AG4F4
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female NPTF
Thread Size	1/2"-14

TECHNICAL SPECIFICATIONS