

## MANNTEK SAFETY BREAK-AWAY COUPLING INDUSTRIAL MALE NPT



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 04/22/2026 08:44 AM

SKU

: 18940

BRAND

: DIXON VALVE

MODEL

: SBC200ALMNPT

### Applications:

Coupling is designed to minimize spillage and damage associated with drive away and pull away incidents.

Typical applications: loading rack

### Features:

Designed to be installed between a fixed point (pipe, pump, manifold) and a hose

Coupling automatically senses an excessive load, closes the valves and disconnects

High flow rate / low pressure drop

### Available Options:

Also available in 150# Flange, BSP thread, DN Flange, 300# ASA Flange, Grooved Ends or any combination thereof. Consult Dixon for more information.

Optional Non-closure Design available, consult Dixon for more information. The non-closure design is an economical alternative which allows the coupling to break away due to pull-away/drive-away incidents thus protecting piping systems and equipment. The design allows spillage of product in these instances due to the lack of valving in the coupling. Useful applications where non-hazardous product is being conveyed and where there are no environmental concerns.

### How it works:

The safety break-away valve consists of two halves, each with a valve that has an O-ring seal. When the safety break-away couplings separate, it allows the valves to close. The two valves close rapidly, minimizing exposure to personnel and the environment.

Safety break-away couplings have three external break bolts. In the case of axial tension all of the bolts take up the force corresponding to the break force

on the hose with a safety margin. Non-axial forces concentrate the tension forces more strongly on one bolt, so that the safety break-away coupling reacts in a natural way to the reduction of the hose break forces.

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

|                            |                        |
|----------------------------|------------------------|
| <b>DN Size</b>             | 50.0                   |
| <b>Factory Part Number</b> | SBC200ALMNPT           |
| <b>Flow</b>                | 200 GPM (757 LPM)      |
| <b>Length</b>              | 7" (178mm)             |
| <b>Material</b>            | Aluminum               |
| <b>Seal</b>                | FKM (FPM)              |
| <b>Size</b>                | 2"                     |
| <b>Weight Lb</b>           | 3.3500                 |
| <b>Width</b>               | 4.5" (114mm)           |
| <b>Working Pressure</b>    | 230 PSI at 70°F (21°C) |