

SINGLE CLAPPER SIAMESE CONNECTION BACK OUTLET

DATE
: 04/24/2026 09:01 AM

SKU
: 19013

BRAND
: DIXON VALVE

MODEL
: SCS4025F

Applications:

Provides the required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply. (250 GPM minimum per inlet.)

Specifications:

UL listed
ULC listed
Factory Mutual approved

Features:

The swing clapper design provides an unobstructed waterway. Exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes.

Construction:

Single swing clapper with (2) pin lug swivel inlets.

Available Options:

Other thread options are available. Consult Dixon for pricing and availability.

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Branding	Auto-Sprinkler
Factory Part Number	SCS4025F
Inlet	(2) 2-1/2" female NST (NH)
Mandatory Pkg/Box Qty	1
Material	Cast Brass
Maximum Operating Pressure	250 PSI
Origin	U.S.
Outlet	4" female NPT
Weight Lb	10.9200