

## SINGLE CLAPPER SIAMESE CONNECTION BACK OUTLET

DATE

: 07/09/2026 08:18 AM

SKU

: 19013

BRAND

: DIXON VALVE

MODEL

: SCS4025F

Applications:

Provides the required 500 GPM minimum to supplement the fire protection as an auxiliary inlet connection to the water supply. (250 GPM minimum per inlet.)

Specifications:

UL listed

ULC listed

Factory Mutual approved

Features:

The swing clapper design provides an unobstructed waterway.

Exposed Fire Department Connections (FDC) provide an economical method of satisfying local fire codes.

Construction:

Single swing clapper with (2) pin lug swivel inlets.

Available Options:

Other thread options are available. Consult Dixon for pricing and availability.

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

|                                   |                            |
|-----------------------------------|----------------------------|
| <b>Branding</b>                   | Auto-Sprinkler             |
| <b>Factory Part Number</b>        | SCS4025F                   |
| <b>Inlet</b>                      | (2) 2-1/2" female NST (NH) |
| <b>Mandatory Pkg/Box Qty</b>      | 1                          |
| <b>Material</b>                   | Cast Brass                 |
| <b>Maximum Operating Pressure</b> | 250 PSI                    |
| <b>Origin</b>                     | U.S.                       |
| <b>Outlet</b>                     | 4" female NPT              |
| <b>Weight Lb</b>                  | 10.9200                    |