

## GROOVE X GROOVE CHECK VALVE



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/02/2026 01:21 PM

SKU

: 27640

BRAND

: DIXON VALVE

MODEL

: SCVV400

Applications:

Single check valves are used in Fire Protection Systems to allow water flow in one direction only.

Typical applications include: at connections between public water supplies and private fire services systems, at discharges from fire pumps, at gravity tank connections, at fire department pumper connections

Use:

For horizontal and vertical installation

Specifications:

UL listed

Construction:

Brass

Supplied with a 1/4" and 1/2" tapped NPT port below the clapper and a 1/4" tapped NPT port above the clapper

Supplied with a 1-1/2" NPT tapped boss below the clapper. Boss above the clapper may be tapped for addition of a 1/2" NPT drain.

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

### TECHNICAL SPECIFICATIONS

<b>Inlet</b>	4" Groove
<b>Material</b>	Brass
<b>Maximum Operating Pressure</b>	250 PSI
<b>Outlet</b>	4" Groove
<b>Factory Part Number</b>	SCVV400
<b>Weight Lb</b>	20.8000