


## SPLIT FLANGE SWIVEL STYLE 20 150# FLANGE



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 07/11/2026 09:06 AM

SKU  
: 19166

BRAND  
: DIXON VALVE

MODEL  
: SF220FGXFGCS00

### Applications:

For use in industries from petroleum, blending plants, petrochemical, refining, mining, distilling, paint plants, farm irrigation and fertilizing, wastewater treatment, food and beverage process equipment, marine and many more

### Features:

Bearing pack design allows easy seal change without removing the ball bearings.

Simple maintenance: remove one nose piece, replace seal pack, and reinstall with little down-time.

Instream seal separates the wetted area from the ball bearings allowing for longer bearing pack life over conventional swivels.

Wide set bearing race for higher moment loads

Compact design for low profile applications

### Construction:

Bearing pack: through hardened forged high carbon alloy

Material contact surfaces: stainless steel or carbon steel nose pieces

### Available Options:

All styles

Stock end configurations: 150 lb. and 300 lb. flanges, FNPT, butt weld, others per request

Stock seals: Baylast™, FKM, PTFE, others per request

Full penetration weld

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	SF220FGXFGCS00
<b>Material</b>	Carbon Steel
<b>Seal</b>	Baylast?
<b>Size</b>	2"
<b>Temperature Range</b>	-35°F to 212°F (-37°C to 100°C)