

SHD-SERIES SCHRADER PNEUMATIC MALE THREADED PLUG



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/24/2026 10:33 AM

SKU
: 19285

BRAND
: DIXON VALVE

MODEL
: SHD2M2

Construction:
Machined components are manufactured using solid bar stock.
Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Compatibility & Interchange Data:
Schrader Twist-Lock Interchange
Parker Twist-Lock, Tomco Series-TL, Foster SHD

Safety notes:
It is important to be safe when installing quick disconnect couplings into a pneumatic circuit. Never install a pneumatic coupling directly into an air tool, use a piece of hose that is at least 18" long, between the tool and the coupling, to prevent damage to the coupling. To protect the operator, safety devices, such as a safety check valve and safety cable should be installed in case there is a hose or coupling failure.

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Burst Pressure	6500 PSI (448 bar)
Factory Part Number	SHD2M2
Hex	11/16"
Length	1.72"
Material	Steel
Maximum OD	0.79"
Maximum Operating Pressure	300 PSI (20 bar)

TECHNICAL SPECIFICATIONS

Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	NPT
Thread Size	1/4"
Weight Lb	0.0500