

## SURELOCK? HOSE END



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/24/2026 01:20 PM

SKU

: 19446

BRAND

: DIXON VALVE

MODEL

: SL075H

### Applications:

Coupling for air service only, commonly used in construction and mining; excels in services where ease, economy, safety and speed are paramount

### Features:

The pressure activated gasket allows easy coupling (less than 15 lbs. of force is required to connect the coupling) and gaskets seal upon introduction of line pressure.

### Construction:

Body: SG iron AS1831 400-250-12

Bellow seal: natural rubber (patent pending)

Safety pin is supplied with each coupling

### Available Options:

Other seal materials are available upon request, contact Dixon.

### Safety notes:

Safety pin is supplied with each coupling and is required as a safety precaution

<sup>1</sup> Pressure rating is based on use with band clamps.

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	SL075H
<b>Material</b>	Iron
<b>Seal</b>	Natural Rubber
<b>Size</b>	3/4"
<b>Style</b>	Small Head
<b>Weight Lb</b>	0.5600
<b>Working Pressure</b>	200 PSIG at 70°F (21°C) <sup>1</sup>