

SURELOCK? THREE WAY CONNECTOR



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/24/2026 01:20 PM

SKU

: 19448

BRAND

: DIXON VALVE

MODEL

: SL09

Applications:

Coupling for air service only, commonly used in construction and mining; excels in services where ease, economy, safety and speed are paramount

Features:

The pressure activated gasket allows easy coupling (less than 15 lbs. of force is required to connect the coupling) and gaskets seal upon introduction of line pressure.

Construction:

Body: SG iron AS1831 400-250-12

Bellow seal: natural rubber (patent pending)

Safety pin is supplied with each coupling

Available Options:

Other seal materials are available upon request, contact Dixon.

Safety notes:

Safety pin is supplied with each coupling and is required as a safety precaution

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|----------------------------|-------------------------|
| Factory Part Number | SL09 |
| Material | Iron |
| Seal | Natural Rubber |
| Size | 1/2" to 1" |
| Style | Small Head |
| Weight Lb | 1.5200 |
| Working Pressure | 200 PSIG at 70°F (21°C) |