


**DQC ST-SERIES SNAP-TITE 71  
INTERCHANGE OLD STYLE  
FEMALE PLUG**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 05/24/2026 01:09 AM

SKU  
: 19752

BRAND  
: DIXON VALVE

MODEL  
: ST16F16-SS

**Construction:**

Machined components are manufactured using solid bar stock  
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Incorporates PTFE or TPC-ET anti-extrusion rings to protect seal components from dynamic impulse damage.

Incorporates PTFE anti-extrusion rings to protect seal components from dynamic impulse damage.

**Available Options:**

Contact Dixon for all available option adders

Oxy-clean treatment is available

**Compatibility & Interchange Data:**

Interchangeable with Snap-Tite 71-Series

**Safety notes:**

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Body Size</b>	2"
<b>Burst Pressure</b>	10000 PSI (700 bar)
<b>Factory Part Number</b>	ST16F16-SS
<b>Hex</b>	3-1/4"
<b>Length</b>	4.50" (114.3mm)
<b>Material</b>	316 Stainless Steel

## TECHNICAL SPECIFICATIONS

<b>Maximum OD</b>	3.48" (88.4mm)
<b>Maximum Operating Pressure</b>	3000 PSI (200 bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	Female NPTF
<b>Thread Size</b>	2" - 11-1/2