


## DQC ST-SERIES SNAP-TITE 71 INTERCHANGE FEMALE PLUG



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 05/23/2026 11:12 PM

SKU  
: 19766

BRAND  
: DIXON VALVE

MODEL  
: ST2F2-SS

### Construction:

Machined components are manufactured using solid bar stock  
Stainless steel balls, retaining rings and springs maximize corrosion resistance and extend service life.

Steel componentry is plated using ROHS Compliant Trivalent Chrome.

Steel nipples are hardened to provide heavy duty performance.

Incorporates PTFE anti-extrusion rings to protect seal components from dynamic impulse damage.

### Available Options:

Contact Dixon for all available option adders

Oxy-clean treatment is available

### Compatibility & Interchange Data:

Interchangeable with Snap-Tite 71-Series

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1/4"
<b>Burst Pressure</b>	28000 PSI (1900 bar)
<b>Factory Part Number</b>	ST2F2-SS
<b>Hex</b>	13/16"
<b>Length</b>	1.84" (46.7mm)
<b>Material</b>	316 Stainless Steel
<b>Maximum OD</b>	0.90" (22.9mm)

## TECHNICAL SPECIFICATIONS

<b>Maximum Operating Pressure</b>	5000 PSI (345 bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	Female NPTF
<b>Thread Size</b>	1/4"-18
<b>Weight Lb</b>	0.2000