


15K THREADED NIPPLE



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 07/08/2026 12:53 AM

SKU

: 21047

BRAND

: DIXON VALVE

MODEL

: TD4F4-SS

Construction:

Machined components are manufactured using 316 stainless steel bar stock
Stainless steel retaining ring to maximize corrosion resistance and extend service life

Seal Components: Nitrile (Buna-N) seals are standard, providing a temperature range of -40°F to 250°F (-40°C to 121°C)

Couplers have a nitrile anti-extrusion ring, providing resistance to o-ring dynamic impulse pressure damage

Compatibility & Interchange Data:

Jet Stream Screw Type

Spir Star CQD Series, DNP CRS Series

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	½?
Factory Part Number	TD4F4-SS
Hex	1-5/8?
Length	2.06?
Material	316 Stainless Steel
Maximum OD	1.75?
Maximum Operating Pressure	15,000 PSI
Temperature Range	-40°F to 250°F (-40°C to 121°C)
Thread	Female NPTF

TECHNICAL SPECIFICATIONS

Thread Size	½" -14
Weight Lb	0.7100