

20K THREADED NIPPLE



DATE
: 05/21/2026 04:09 PM

SKU
: 21048

BRAND
: DIXON VALVE

MODEL
: TD4PF4.5-SS

Construction:

Machined components are manufactured using 316 stainless steel bar stock
Stainless steel retaining ring to maximize corrosion resistance and extend service life

Seal Components: Nitrile (Buna-N) seals are standard, providing a temperature range of -40°F to 250°F (-40°C to 121°C)

Couplers have a nitrile anti-extrusion ring, providing resistance to O-ring dynamic impulse pressure damage

Compatibility & Interchange Data:

Jet Stream Screw Type

Spir Star CQD Series, DNP CRS Series

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	1/2"
Factory Part Number	TD4PF4.5-SS
Hex	1-1/8" Flat
Length	2.40"
Material	316 Stainless Steel
Maximum OD	1.74"
Maximum Operating Pressure	20,000 PSI
Temperature Range	-40°F to 250°F (-40°C to 121°C)
Thread	9/16" Female MP

* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Thread Size

13/16"-16