

TECTITE[®] BY APOLLO[®] PUSH TO CONNECT REDUCING COUPLING

DATE
: 06/13/2026 04:06 PM

SKU
: 21426



BRAND
: DIXON VALVE

MODEL
: U058



Use:
Connects copper, CPVC, PEX, PE-RT pipe in any combination

Specifications:
Certified and listed to ASSE1061, ANSI/NSF 61, and ANSI/NSF 14
Listed by IAPMO
Meets UPC, IPC and cUPC requirements

Features:
No soldering, clamps, unions or glue needed
Integral tube liner required for PEX and PE-RT installations
Easy to disconnect if needed
Can be rotated after assembly for easier installation in tight spaces

Construction:
All Tectite[™] by Apollo[®] fittings are lead free

Compatibility & Interchange Data:
Comparable to Sharkbite[®]

Safety notes:
For water, dry, clean air or 100% glycol solutions only, vacuum
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

* Referential image
** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Factory Part Number	U058
Material	Forged Brass
Maximum Operating Pressure	200 PSI
Temperature Range	32°F - 250°F (0°C - 121°C)
Tube Size	3/4" x 1/2"
Weight Lb	0.1600