

## TECTITE<sup>®</sup> BY APOLLO<sup>®</sup> PUSH TO CONNECT REDUCING COUPLING

DATE  
: 04/27/2026 09:44 AM

SKU  
: 21427



BRAND  
: DIXON VALVE

MODEL  
: U060



Use:  
Connects copper, CPVC, PEX, PE-RT pipe in any combination

Specifications:  
Certified and listed to ASSE1061, ANSI/NSF 61, and ANSI/NSF 14  
Listed by IAPMO  
Meets UPC, IPC and cUPC requirements

Features:  
No soldering, clamps, unions or glue needed  
Integral tube liner required for PEX and PE-RT installations  
Easy to disconnect if needed  
Can be rotated after assembly for easier installation in tight spaces

Construction:  
All Tectite<sup>™</sup> by Apollo<sup>®</sup> fittings are lead free

Compatibility & Interchange Data:  
Comparable to Sharkbite<sup>®</sup>

Safety notes:  
For water, dry, clean air or 100% glycol solutions only, vacuum  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\* Referential image  
\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

|                                   |                            |
|-----------------------------------|----------------------------|
| <b>Factory Part Number</b>        | U060                       |
| <b>Material</b>                   | Forged Brass               |
| <b>Maximum Operating Pressure</b> | 200 PSI                    |
| <b>Temperature Range</b>          | 32°F - 250°F (0°C - 121°C) |
| <b>Tube Size</b>                  | 1" x 3/4"                  |
| <b>Weight Lb</b>                  | 0.2500                     |