

## TECTITE? BY APOLLO® PUSH TO CONNECT REDUCING FEMALE CONNECTOR



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 06/13/2026 03:00 PM

SKU

: 21428

BRAND

: DIXON VALVE

MODEL

: U068

Use:

Connects copper, CPVC, PEX, PE-RT pipe in any combination

Specifications:

Certified and listed to ASSE1061, ANSI/NSF 61, and ANSI/NSF 14

Listed by IAPMO

Meets UPC, IPC and cUPC requirements

Features:

No soldering, clamps, unions or glue needed

Integral tube liner required for PEX and PE-RT installations

Easy to disconnect if needed

Can be rotated after assembly for easier installation in tight spaces

Construction:

All Tectite™ by Apollo® fittings are lead free

Compatibility & Interchange Data:

Comparable to Sharkbite®

Safety notes:

For water, dry, clean air or 100% glycol solutions only, vacuum

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	U068
<b>Female Thread</b>	NPT
<b>Female Thread Size</b>	3/4"
<b>Material</b>	Forged Brass
<b>Maximum Operating Pressure</b>	200 PSI
<b>Temperature Range</b>	32°F - 250°F (0°C - 121°C)
<b>Thread</b>	NPT
<b>Tube Size</b>	1/2"
<b>Weight Lb</b>	0.2300