

TECTITE? BY APOLLO® PUSH TO CONNECT STRAIGHT MALE CONNECTOR

DATE
: 04/27/2026 11:25 AM

SKU
: 21434



BRAND
: DIXON VALVE

MODEL
: U134



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

Use:
Connects copper, CPVC, PEX, PE-RT pipe in any combination

Specifications:
Certified and listed to ASSE1061, ANSI/NSF 61, and ANSI/NSF 14
Listed by IAPMO
Meets UPC, IPC and cUPC requirements

Features:
No soldering, clamps, unions or glue needed
Integral tube liner required for PEX and PE-RT installations
Easy to disconnect if needed
Can be rotated after assembly for easier installation in tight spaces

Construction:
All Tectite™ by Apollo® fittings are lead free

Compatibility & Interchange Data:
Comparable to Sharkbite®

Safety notes:
For water, dry, clean air or 100% glycol solutions only, vacuum
WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Factory Part Number	U134
Male Thread	NPT
Male Thread Size	3/4"
Material	Forged Brass
Maximum Operating Pressure	200 PSI
Temperature Range	32°F - 250°F (0°C - 121°C)
Thread	NPT
Tube Size	3/4"
Weight Lb	0.2100