

## TECTITE? BY APOLLO® PUSH TO CONNECT STRAIGHT MALE CONNECTOR



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 06/13/2026 05:39 PM

SKU  
: 21435

BRAND  
: DIXON VALVE

MODEL  
: U140

Use:  
Connects copper, CPVC, PEX, PE-RT pipe in any combination

Specifications:  
Certified and listed to ASSE1061, ANSI/NSF 61, and ANSI/NSF 14  
Listed by IAPMO  
Meets UPC, IPC and cUPC requirements

Features:  
No soldering, clamps, unions or glue needed  
Integral tube liner required for PEX and PE-RT installations  
Easy to disconnect if needed  
Can be rotated after assembly for easier installation in tight spaces

Construction:  
All Tectite™ by Apollo® fittings are lead free

Compatibility & Interchange Data:  
Comparable to Sharkbite®

Safety notes:  
For water, dry, clean air or 100% glycol solutions only, vacuum  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

|                                   |                            |
|-----------------------------------|----------------------------|
| <b>Factory Part Number</b>        | U140                       |
| <b>Male Thread</b>                | NPT                        |
| <b>Male Thread Size</b>           | 1"                         |
| <b>Material</b>                   | Forged Brass               |
| <b>Maximum Operating Pressure</b> | 200 PSI                    |
| <b>Temperature Range</b>          | 32°F - 250°F (0°C - 121°C) |
| <b>Thread</b>                     | NPT                        |
| <b>Tube Size</b>                  | 1"                         |
| <b>Weight Lb</b>                  | 0.3300                     |