

## TECTITE? BY APOLLO® PUSH TO CONNECT ELBOW



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 04/27/2026 09:45 AM

SKU  
: 21438

BRAND  
: DIXON VALVE

MODEL  
: U260

Use:  
Connects copper, CPVC, PEX, PE-RT pipe in any combination  
Approved for use underground and behind walls without access panels

Specifications:  
Certified and listed to ASSE1061, ANSI/NSF 61, and ANSI/NSF 14  
Listed by IAPMO  
Meets UPC, IPC and cUPC requirements

Features:  
No soldering, clamps, unions or glue needed  
Integral tube liner for PEX installations  
Easy to disconnect if needed  
Can be rotated after assembly for easier installation in tight spaces

Construction:  
All Tectite™ by Apollo® fittings are lead free

Compatibility & Interchange Data:  
Comparable to Sharkbite®

Safety notes:  
For water, dry, clean air or 100% glycol solutions only, vacuum  
WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**TECHNICAL SPECIFICATIONS**

<b>Factory Part Number</b>	U260
<b>Material</b>	Forged Brass
<b>Maximum Operating Pressure</b>	200 PSI
<b>Temperature Range</b>	32°F - 250°F (0°C - 121°C)
<b>Tube Size</b>	1"
<b>Weight Lb</b>	0.4800