

DQC V-SERIES SNAP-TITE H/H INTERCHANGE VALVED MALE PLUG



DATE
: 05/24/2026 08:30 PM

SKU
: 21479

BRAND
: DIXON VALVE

MODEL
: V10M10-SS

Features:

General purpose hydraulic quick-connect provides superior flow characteristics with built-in reliability

Construction:

Machined components are manufactured using solid bar stock

Available Options:

Contact Dixon for all available option adders

Standard seal options include: FKM, EPDM, Steam-EP, FDA FKM, Mil-Nitrile, Fuel Nitrile and Silicone

Kalrez® seal options include: 4079, 6375 and 7075

Valve options include: Unvalved, tubular, steel, brass and 316 stainless steel

Sleeve options include: Sleeve-lock, Flanged and Silicone-flanged

Oxy-clean treatment is available

Compatibility & Interchange Data:

Interchangeable to MIL-C-51234

Snap-Tite H and Faster TNV

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Body Size	1-1/4"
Burst Pressure	3000 PSI (200 bar)
Factory Part Number	V10M10-SS
Hex	2"
Length	3.46" (87.9mm)
Material	316 Stainless Steel
Maximum OD	2.19" (55.6mm)
Maximum Operating Pressure	1500 PSI (100 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Male NPTF
Thread Size	1-1/4" - 1-1/2"
Weight Lb	1.3500