


**DQC V-SERIES SNAP-TITE H/H
INTERCHANGE VALVED
FEMALE PLUG**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/24/2026 04:31 PM

SKU
: 21481

BRAND
: DIXON VALVE

MODEL
: V10OF10

Features:

General purpose hydraulic quick-connect provides superior flow characteristics with built-in reliability

Construction:

Steel nipples are machined from high-strength steel and induction hardened.

Available Options:

Contact Dixon for all available option adders

Standard seal options include: FKM, EPDM, Steam-EP, FDA FKM, Mil-Nitrile, Fuel Nitrile and Silicone

Kalrez® seal options include: 4079, 6375 and 7075

Valve options include: Unvalved, tubular, steel, brass and 316 stainless steel

Sleeve options include: Sleeve-lock, Flanged and Silicone-flanged

Oxy-clean treatment is available

Compatibility & Interchange Data:

Interchangeable to MIL-C-51234

Snap-Tite H and Faster TNV

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

| | |
|-----------------------------------|-----------------------------------|
| Body Size | 1-1/4" |
| Burst Pressure | 5000 PSI (345 bar) |
| Factory Part Number | V10OF10 |
| Hex | 2" |
| Length | 3.41" (86.6mm) |
| Material | Steel |
| Maximum OD | 2.19" (55.6mm) |
| Maximum Operating Pressure | 1750 PSI (120 bar) |
| Temperature Range | -40°F to +250°F (-40°C to +121°C) |
| Thread | Female ORB |
| Thread Size | 1-5/8"-12 |
| Weight Lb | 0.5900 |