


**DQC V-SERIES SNAP-TITE H/H  
INTERCHANGE VALVED  
FEMALE PLUG**



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE  
: 05/24/2026 04:31 PM

SKU  
: 21483

BRAND  
: DIXON VALVE

MODEL  
: V12BF12-B

Features:

General purpose hydraulic quick-connect provides superior flow characteristics with built-in reliability

Construction:

Machined components are manufactured using solid bar stock

Available Options:

Contact Dixon for all available option adders

Standard seal options include: FKM, EPDM, Steam-EP, FDA FKM, Mil-Nitrile, Fuel Nitrile and Silicone

Kalrez® seal options include: 4079, 6375 and 7075

Valve options include: Unvalved, tubular, steel, brass and 316 stainless steel

Sleeve options include: Sleeve-lock, Flanged and Silicone-flanged

Oxy-clean treatment is available

Compatibility & Interchange Data:

Interchangeable to MIL-C-51234

Snap-Tite H and Faster TNV

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1-1/2"
<b>Burst Pressure</b>	1200 PSI (80 bar)
<b>Factory Part Number</b>	V12BF12-B
<b>Hex</b>	2-1/2"
<b>Length</b>	3.35" (79.0mm)
<b>Material</b>	Brass
<b>Maximum OD</b>	2.74" (69.6mm)
<b>Maximum Operating Pressure</b>	350 PSI (24 bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	Female BSPP
<b>Thread Size</b>	1-1/2"-11
<b>Weight Lb</b>	2.2500