


**DQC V-SERIES SNAP-TITE H/H
INTERCHANGE VALVED
FEMALE PLUG**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE
: 05/24/2026 05:38 PM

SKU
: 21499

BRAND
: DIXON VALVE

MODEL
: V16BF16-B

Features:

General purpose hydraulic quick-connect provides superior flow characteristics with built-in reliability

Construction:

Machined components are manufactured using solid bar stock

Available Options:

Contact Dixon for all available option adders

Standard seal options include: FKM, EPDM, Steam-EP, FDA FKM, Mil-Nitrile, Fuel Nitrile and Silicone

Kalrez® seal options include: 4079, 6375 and 7075

Valve options include: Unvalved, tubular, steel, brass and 316 stainless steel

Sleeve options include: Sleeve-lock, Flanged and Silicone-flanged

Oxy-clean treatment is available

Compatibility & Interchange Data:

Interchangeable to MIL-C-51234

Snap-Tite H and Faster TNV

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	2"
Burst Pressure	1000 PSI (70 bar)
Factory Part Number	V16BF16-B
Hex	3-1/2"
Length	3.72" (94.5mm)
Material	Brass
Maximum OD	3.83" (97.3mm)
Maximum Operating Pressure	400 PSI (28 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female BSPP
Thread Size	2"-11
Weight Lb	4.7500