

DQC V-SERIES SNAP-TITE H/H INTERCHANGE VALVED MALE PLUG



DATE
: 05/24/2026 09:33 PM

SKU
: 21532

BRAND
: DIXON VALVE

MODEL
: V2M1

Features:

General purpose hydraulic quick-connect provides superior flow characteristics with built-in reliability

Construction:

Steel nipples are machined from high-strength steel and induction hardened.

Available Options:

Contact Dixon for all available option adders

Standard seal options include: FKM, EPDM, Steam-EP, FDA FKM, Mil-Nitrile, Fuel Nitrile and Silicone

Kalrez® seal options include: 4079, 6375 and 7075

Valve options include: Unvalved, tubular, steel, brass and 316 stainless steel

Sleeve options include: Sleeve-lock, Flanged and Silicone-flanged

Oxy-clean treatment is available

Compatibility & Interchange Data:

Interchangeable to MIL-C-51234

Snap-Tite H and Faster TNV

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

TECHNICAL SPECIFICATIONS

Body Size	1/4"
Burst Pressure	12700 PSI (876 bar)
Factory Part Number	V2M1
Hex	7/8"
Length	2.06"
Material	Steel
Maximum OD	0.97"
Maximum Operating Pressure	6500 PSI (450 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Male NPTF
Thread Size	1/8"-27
Weight Lb	0.1600