

## DQC V-SERIES SNAP-TITE H/H INTERCHANGE VALVED MALE PLUG



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/24/2026 09:33 PM

SKU

: 21533

BRAND

: DIXON VALVE

MODEL

: V2M2

Features:

General purpose hydraulic quick-connect provides superior flow characteristics with built-in reliability

Construction:

Steel nipples are machined from high-strength steel and induction hardened.

Available Options:

Contact Dixon for all available option adders

Standard seal options include: FKM, EPDM, Steam-EP, FDA FKM, Mil-Nitrile, Fuel Nitrile and Silicone

Kalrez® seal options include: 4079, 6375 and 7075

Valve options include: Unvalved, tubular, steel, brass and 316 stainless steel

Sleeve options include: Sleeve-lock, Flanged and Silicone-flanged

Oxy-clean treatment is available

Compatibility & Interchange Data:

Interchangeable to MIL-C-51234

Snap-Tite H and Faster TNV

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1/4"
<b>Burst Pressure</b>	12700 PSI (876 bar)
<b>Factory Part Number</b>	V2M2
<b>Hex</b>	7/8"
<b>Length</b>	2.06" (52.3mm)
<b>Material</b>	Steel
<b>Maximum OD</b>	0.97" (24.6mm)
<b>Maximum Operating Pressure</b>	6500 PSI (450 bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	Male NPTF
<b>Thread Size</b>	1/4"-18
<b>Weight Lb</b>	0.1600