

## DQC V-SERIES SNAP-TITE H/H INTERCHANGE VALVED MALE PLUG



DATE  
: 05/24/2026 09:34 PM

SKU  
: 21562

BRAND  
: DIXON VALVE

MODEL  
: V3M3-SS

**Features:**

General purpose hydraulic quick-connect provides superior flow characteristics with built-in reliability

**Construction:**

Machined components are manufactured using solid bar stock

**Available Options:**

Contact Dixon for all available option adders

Standard seal options include: FKM, EPDM, Steam-EP, FDA FKM, Mil-Nitrile, Fuel Nitrile and Silicone

Kalrez® seal options include: 4079, 6375 and 7075

Valve options include: Unvalved, tubular, steel, brass and 316 stainless steel

Sleeve options include: Sleeve-lock, Flanged and Silicone-flanged

Oxy-clean treatment is available

**Compatibility & Interchange Data:**

Interchangeable to MIL-C-51234

Snap-Tite H and Faster TNV

**Safety notes:**

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

**TECHNICAL SPECIFICATIONS**

<b>Body Size</b>	3/8"
<b>Burst Pressure</b>	8000 PSI (550 bar)
<b>Factory Part Number</b>	V3M3-SS
<b>Hex</b>	1"
<b>Length</b>	2.25" (57.2mm)
<b>Material</b>	316 Stainless Steel
<b>Maximum OD</b>	1.10" (27.9mm)
<b>Maximum Operating Pressure</b>	4000 PSI (275 bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	Male NPTF
<b>Thread Size</b>	3/8"-18
<b>Weight Lb</b>	0.2200