

**DQC V-SERIES SNAP-TITE H/H
INTERCHANGE VALVED
FEMALE PLUG**



* Referential image

** Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/24/2026 06:43 PM

SKU

: 21564

BRAND

: DIXON VALVE

MODEL

: V3OF3

Features:

General purpose hydraulic quick-connect provides superior flow characteristics with built-in reliability

Construction:

Steel nipples are machined from high-strength steel and induction hardened.

Available Options:

Contact Dixon for all available option adders

Standard seal options include: FKM, EPDM, Steam-EP, FDA FKM, Mil-Nitrile, Fuel Nitrile and Silicone

Kalrez® seal options include: 4079, 6375 and 7075

Valve options include: Unvalved, tubular, steel, brass and 316 stainless steel

Sleeve options include: Sleeve-lock, Flanged and Silicone-flanged

Oxy-clean treatment is available

Compatibility & Interchange Data:

Interchangeable to MIL-C-51234

Snap-Tite H and Faster TNV

Safety notes:

WARNING: Cancer and Reproductive Harm- www.P65Warnings.ca.gov

TECHNICAL SPECIFICATIONS

Body Size	3/8"
Burst Pressure	10500 PSI (700 bar)
Factory Part Number	V3OF3
Hex	1"
Length	1.94" (49.3mm)
Material	Steel
Maximum OD	1.10" (27.9mm)
Maximum Operating Pressure	4500 PSI (310 bar)
Temperature Range	-40°F to +250°F (-40°C to +121°C)
Thread	Female ORB
Thread Size	9/16"-18
Weight Lb	0.2500