

## KING CABLE® HOSE-TO-HOSE SERVICE WITH COPPER FERRULE



DATE  
: 07/08/2026 01:48 AM

SKU  
: 25628

BRAND  
: DIXON VALVE

MODEL  
: WA2B



### Applications:

When hose, couplings or clamps fail, or there is an accidental separation of the assembly, King safety cables minimize damage to equipment and injuries to operators.

### Use:

WA2 with bronze/copper ferrule for special environmental conditions

### Features:

King cable is the low cost answer to eliminate injuries caused by broken air hose connections

King safety cable reaches across the hose fittings to provide standby safety for hose. Spring-loaded loops in the cable ends open easily to pass over the couplings for a firm grip on the hose.

Thoroughly tested with years of service. A positive safeguard for air hose connections- helps you meet today's safety standards.

Highly resistant to rust and corrosion

### Construction:

Wire Rope: Galvanized Carbon Steel

Ferrules: Copper

Springs: Galvanized Carbon Steel

### Installation

Must be installed in the extended position (no slack)

No tools needed- easy to install and remove

### Note:

Cables are shipped with safety restraint labels attached

### Safety notes:

\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

King Safety cable must be installed in the extended position (no slack)

The Canada Occupational Safety and Health regulations Part XIII, 13:6b states: "Where an air hose is connected to a portable air powered tool used by an employee, a restraining device shall be attached to all hose connections, in order to prevent injury to an employee in the even of an accidental disconnection of a hose."

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Factory Part Number</b>	WA2B
<b>Hose ID</b>	1-1/2" - 3" (38mm - 75mm)
<b>Length</b>	38" (965mm)
<b>Material</b>	Galvanized Carbon Steel with Copper Ferrule
<b>Maximum Operating Pressure</b>	200 PSI
<b>Size</b>	1/4" cable (6mm cable)
<b>Weight Lb</b>	2.0000