


## WS-SERIES HIGH PRESSURE WINGSTYLE FEMALE PLUG



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 06/16/2026 07:29 AM

SKU

: 25657

BRAND

: DIXON VALVE

MODEL

: WS10F10

Applications:

Used extensively in oil field and off shore oil rig applications

Construction:

Machined components are manufactured using solid steel bar stock.

Stainless steel retaining rings and springs maximize corrosion resistance and extend service life.

Steel componentry is plated using ROHS Compliant Zinc Nickel for superior corrosion resistance.

Nitrile (Buna-N) seals are standard, providing a temperature range of -40°F to +250°F (-40°C to +121°C)

PTFE anti-extrusion ring protects main coupling O-Ring from dynamic impulse pressure damage.

Main valve seal is 'housed' to improve seal integrity during pressurized connection/disconnection.

Compatibility & Interchange Data:

Snap-Tite 75-Series, Hydraulics Inc. Series- 5TV, DNP VFF-HD

Stucchi VOF, Faster OGV, Eaton FD85, Holmbury LC

Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

<b>Body Size</b>	1-1/4"
<b>Burst Pressure</b>	25100 PSI (1700 bar)
<b>Factory Part Number</b>	WS10F10
<b>Length</b>	5.38" (136.7mm)
<b>Material</b>	Steel
<b>Maximum OD</b>	2.63" (66.8mm)
<b>Maximum Operating Pressure</b>	5000 PSI (345 bar)
<b>Temperature Range</b>	-40°F to +250°F (-40°C to +121°C)
<b>Thread</b>	Female NPTF
<b>Thread Size</b>	1-1/4" - 11-1/2
<b>Weight Lb</b>	4.2000