


## DQC WS-BOP SERIES HIGH PRESSURE WINGSTYLE FEMALE PLUG



\* Referential image

\*\* Some features may vary without prior notice. Sale subject to inventory availability

DATE

: 05/25/2026 06:56 AM

SKU

: 25666

BRAND

: DIXON VALVE

MODEL

: WS12F12-BOP

### Applications:

Designed for use in oil rig BOP systems where couplings are required to operate under fire conditions in an emergency.

### Specifications:

BOP Couplings have been fire tested and Lloyd's certified to 700°C (1300°F) in accordance with API 16D. Certificate available upon request.

Lloyd's Test Pressure: 5,000 PSI

### Construction:

Machined components are manufactured using solid steel bar stock.

Stainless steel retaining rings and springs maximize corrosion resistance and extend service life.

Steel componentry is plated using ROHS Compliant Zinc Nickel

Red powder coated external nipple O-ring for easy BOP service identification.

Blow-out Preventer (BOP) couplings contain severe service FKM seals

PTFE anti-extrusion ring protects main coupling O-Ring from dynamic impulse pressure damage.

Main valve seal is 'housed' to improve seal integrity during pressurized connection/disconnection.

### Compatibility & Interchange Data:

Snap-Tite 75-Series

DNP VFF-HD BOP series

### Safety notes:

WARNING: Cancer and Reproductive Harm- [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

## TECHNICAL SPECIFICATIONS

|                                   |                      |
|-----------------------------------|----------------------|
| <b>Body Size</b>                  | 1-1/2"               |
| <b>Burst Pressure</b>             | 20000 PSI (1400 bar) |
| <b>Factory Part Number</b>        | WS12F12-BOP          |
| <b>Length</b>                     | 5.98"                |
| <b>Material</b>                   | Steel                |
| <b>Maximum OD</b>                 | 3.25"                |
| <b>Maximum Operating Pressure</b> | 5000 PSI (345 bar)   |
| <b>Thread</b>                     | Female NPTF          |
| <b>Thread Size</b>                | 1-1/2" - 1 1-1/2"    |
| <b>Weight Lb</b>                  | 7.0000               |